

# SmartRamps

## WHEELCHAIR RAMPS



Wheelchair ramps for minivans or full-size vans make it easier to transport wheelchair passengers, speeding up entry and exiting considerably. SmartRamps are available in a range of lengths and widths. They are produced using perforated aluminum metal profiles that are lightweight, non-slip and ultra-strong. These ramps are available as straight fold-up or swivel-mounted.

- Center-folding.
- Fitted with quick locking system.
- Robust: 20G collision-tested.
- Weight ranges from 77 lbs-101 lbs (35 kgs. - 46 kgs.) Depends on type.
- Easy operation with two handles and pneumatic absorber.
- Non-slip surface.
- Aluminum profile.
- Single-hand operation.
- Option: 90° opening.
- Weight capacity:
  - Standard: 660 lbs. / 300 kgs.
  - Extra load capacity available: 440 lbs. / 200 kgs.
  - Total Capacity: 1100 lbs. / 500 kgs.



### Standards

AMF-Bruns of America's SmartRamps meets ADA regulations.



# SMARTRAMPS

Part #	Ramp	Version	A Outside Trim Width	B Usable Width	C Trim Overall Width	D Trim Length	E Usable Length	F Height of Edges	G Frame Depth	Load	Option: Extra Support
H20101	2400 mm x 600 mm 94.5" x 23.6"	Standard	640 mm 25.20"	600 mm 23.62"	830 mm 32.68"	1230 mm 48.43"	2390 mm 94.09"	60 mm 2.36"	215 mm 8.46"	300 kg 660 lbs	500 kg 1102 lbs
H20101T	2400 mm x 600 mm 94.5" x 23.6"	Swivel	640 mm 25.20"	600 mm 23.62"	970 mm 38.19"	1245 mm 49.02"	2390 mm 94.09"	60 mm 2.36"	215 mm 8.46"	300 kg 660 lbs	500 kg 1102 lbs
H20104	2400 mm x 700 mm 94.5" x 23.6"	Standard	740 mm 29.13"	700 mm 27.56"	930 mm 36.61"	1230 mm 48.43"	2390 mm 94.09"	60 mm 2.36"	215 mm 8.46"	300 kg 660 lbs	500 kg 1102 lbs
H20104T	2400 mm x 700 mm 94.5" x 23.6"	Swivel	740 mm 29.13"	700 mm 27.56"	1070 mm 42.13"	2045 mm 80.51"	2390 mm 94.09"	60 mm 2.36"	215 mm 8.46"	300 kg 660 lbs	500 kg 1102 lbs
H20107	2400 mm x 900 mm 94.5" x 35.4"	Standard	950 mm 37.40"	910 mm 35.83"	1140 mm 44.88"	1230 mm 48.43"	2390 mm 94.09"	80 mm 3.15"	230 mm 9.05"	300 kg 660 lbs	500 kg 1102 lbs
H20107T	2400 mm x 900 mm 94.5" x 35.4"	Swivel	950 mm 37.40"	910 mm 35.83"	1280 mm 50.39"	1245 mm 49.02"	2390 mm 94.09"	80 mm 3.15"	230 mm 9.05"	300 kg 660 lbs	500 kg 1102 lbs
H20110	2400 mm x 800 mm 94.5" x 31.5"	Standard	840 mm 33.07"	800 mm 31.5"	1030 mm 40.55"	1230 mm 48.43"	2390 mm 94.09"	60 mm 2.36"	215 mm 8.46"	300 kg 660 lbs	500 kg 1102 lbs
H20110T	2400 mm x 800 mm 94.5" x 31.5"	Swivel	840 mm 33.07"	800 mm 31.5"	1170 mm 46.06"	1245 mm 49.02"	2390 mm 94.09"	60 mm 2.36"	215 mm 8.46"	300 kg 660 lbs	500 kg 1102 lbs
H20114	2800 mm x 900 mm 110" x 35.4"	Standard	950 mm 37.40"	910 mm 35.83"	1140 mm 44.88"	1430 mm 56.30"	2780 mm 109.45"	100 mm 3.94"	245 mm 9.65"	300 kg 660 lbs	500 kg 1102 lbs
H20114T	2800 mm x 900 mm 110" x 35.4"	Swivel	950 mm 37.40"	910 mm 35.83"	1280 mm 50.39"	1440 mm 56.69"	2780 mm 109.45"	100 mm 3.94"	245 mm 9.65"	300 kg 660 lbs	500 kg 1102 lbs
H20115	2000 mm x 800 mm 78.7" x 31.5"	Standard	840 mm 33.07"	800 mm 31.50"	1030 mm 40.55"	1030 mm 40.55"	1190 mm 46.85"	60 mm 2.36"	215 mm 8.46"	300 kg 660 lbs	500 kg 1102 lbs
H20115T	2000 mm x 800 mm 78.7" x 31.5"	Swivel	840 mm 33.07"	800 mm 31.50"	1170 mm 46.06"	1045 mm 41.14"	1190 mm 46.85"	60 mm 2.36"	215 mm 8.46"	300 kg 660 lbs	500 kg 1102 lbs



## AMF-Bruns of America

1797 Georgetown Road • Hudson, OH 44236  
877-506-3770 • [www.amfbrunsamerica.com](http://www.amfbrunsamerica.com)

